

View Online at <https://aerobasegroup.com/nsn/5930-01-278-3434>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.235 inches single mounting facility and 0.265 inches single mounting facility

**Width Between Flats:**

0.182 inches single actuator and 0.184 inches single actuator

**Overall Length:**

Between 1.422 inches and 1.452 inches

**First Flat Length:**

0.146 inches single actuator and 0.166 inches single actuator

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

0.485 inches single actuator and 0.515 inches single actuator

**Overall Diameter:**

Between 0.937 inches and 1.047 inches

**Nonturn Device Radius:**

0.531 inches at 6: 00 o'clock

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Tab at 6: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

2 each section front

**Throw Quantity:**

7 each section rear

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

7 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

200.0 milliamperes resistive load dc at sea level

**Precious Material And Location:**

Contacts and clips silver and clip surfaces gold

**Precious Material:**

Silver and gold

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0