

View Online at <https://aerobasegroup.com/nsn/5930-01-278-3437>

Body Style:

Bushing mount

Bushing Length:

Between 0.463 inches and 0.473 inches

Body Length:

0.843 inches

Body Width:

0.450 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.453 inches and 0.484 inches

Actuator Height:

Between 0.235 inches and 0.245 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

Between 0.490 inches and 0.520 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0