

View Online at <https://aerobasegroup.com/nsn/5930-01-278-4973>

Thread Class:

2a

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Waterproof

Overall Length:

1.375 inches

Overall Height:

0.668 inches

Overall Width:

0.668 inches

Body Diameter:

0.562 inches

Bushing Length:

Between 0.297 inches and 0.327 inches

Body Length:

0.440 inches

Case Material:

Metal

Actuator Diameter:

Between 0.360 inches and 0.390 inches

Actuator Height:

Between 0.235 inches and 0.265 inches

Actuator Color:

Black single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

6625-01-257-7921 test set

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0