NSN 5930-01-279-0996

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-279-0996

| Body Style: |
|--|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Explosion proof |
| Overall Length: |
| 11.690 inches |
| Overall Height: |
| 3.250 inches |
| Overall Width: |
| 5.565 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 2.500 inches |
| Actuator Style: |
| Roller arm |
| Actuator Height: |
| 3.250 inches |
| Actuator Roller Diameter: |
| 1.000 inches |
| Actuator Roller Width: |
| 0.250 inches |
| Housing Height: |
| 3.250 inches |
| Housing Length: |
| 9.500 inches |
| Housing Width: |
| 4.690 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 8.500 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 3.630 inches |
| Maximum Voltage Rating In Volts: |
| 440.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

500.000 milliamperes inductive dc and 1.500 amperes inductive ac

NSN 5930-01-279-0996

Sensitive Switch - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 8 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A053a0