NSN 5930-01-279-0996

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-279-0996

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
11.690 inches
Overall Height:
3.250 inches
Overall Width:
5.565 inches
Case Material:
Metal
Actuator Length:
2.500 inches
Actuator Style:
Roller arm
Actuator Height:
3.250 inches
Actuator Roller Diameter:
1.000 inches
Actuator Roller Width:
0.250 inches
Housing Height:
3.250 inches
Housing Length:
9.500 inches
Housing Width:
4.690 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
8.500 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
3.630 inches
Maximum Voltage Rating In Volts:
440.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:

500.000 milliamperes inductive dc and 1.500 amperes inductive ac

NSN 5930-01-279-0996

Sensitive Switch - Page 2 of 2



Terminal Type And Quantity:
8 screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0