

View Online at <https://aerobasegroup.com/nsn/5930-01-279-2113>

Thread Class:

3a single pressure connection

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

3.300 inches

Outside Diameter:

0.438 inches single connection

Overall Diameter:

0.880 inches

Pressure Switch Type:

Absolute

Width Across Flats:

0.680 inches

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

450.00 pounds per square inch gage

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

1200.00 pounds per square inch gage

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

1.2 amperes resistive load single voltage and 660.0 milliamperes inductive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

222.10 actuation point pounds per square inch absolute and 157.10 deactuation point pounds per square inch absolute

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0