

View Online at <https://aerobasegroup.com/nsn/5930-01-279-2116>

**Body Style:**

Bushing mount

**Overall Length:**

Between 0.490 inches and 0.510 inches

**Overall Height:**

Between 1.809 inches and 1.829 inches

**Overall Width:**

Between 0.440 inches and 0.460 inches

**Bushing Length:**

Between 0.284 inches and 0.304 inches

**Body Length:**

Between 0.490 inches and 0.510 inches

**Body Width:**

Between 0.440 inches and 0.460 inches

**Body Height:**

Between 0.835 inches and 0.855 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.120 inches and 0.140 inches

**Actuator Height:**

Between 0.610 inches and 0.630 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Maximum Voltage Rating In Volts:**

20.0 dc

**End Application:**

5895-01-133-6600 control, communication

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

200.000 milliamperes resistive dc

**Precious Material And Location:**

Contact and terminal surfaces gold

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A053a0