

View Online at <https://aerobasegroup.com/nsn/5930-01-279-2116>

Body Style:

Bushing mount

Overall Length:

Between 0.490 inches and 0.510 inches

Overall Height:

Between 1.809 inches and 1.829 inches

Overall Width:

Between 0.440 inches and 0.460 inches

Bushing Length:

Between 0.284 inches and 0.304 inches

Body Length:

Between 0.490 inches and 0.510 inches

Body Width:

Between 0.440 inches and 0.460 inches

Body Height:

Between 0.835 inches and 0.855 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.120 inches and 0.140 inches

Actuator Height:

Between 0.610 inches and 0.630 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Maximum Voltage Rating In Volts:

20.0 dc

End Application:

5895-01-133-6600 control, communication

Inclosure Type:

Fully enclosed

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.250 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

200.000 milliamperes resistive dc

Precious Material And Location:

Contact and terminal surfaces gold

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0