

View Online at <https://aerobasegroup.com/nsn/5930-01-279-3715>

Thread Class:

2a

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 1.235 inches and 1.265 inches

Overall Height:

Between 2.080 inches and 2.110 inches

Overall Width:

Between 0.673 inches and 0.703 inches

Bushing Length:

Between 0.454 inches and 0.484 inches

Body Width:

Between 0.673 inches and 0.703 inches

Body Height:

Between 0.672 inches and 0.702 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.237 inches and 0.243 inches

Actuator Height:

Between 0.673 inches and 0.703 inches

Actuator Position-action Relationship:

Up position momentary and down position maintained

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 1.500 amperes inductive dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac

Precious Material And Location:

Terminal surfaces silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

27914-2088678 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0