

View Online at <https://aerobasegroup.com/nsn/5930-01-279-3715>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Dustproof

**Overall Length:**

Between 1.235 inches and 1.265 inches

**Overall Height:**

Between 2.080 inches and 2.110 inches

**Overall Width:**

Between 0.673 inches and 0.703 inches

**Bushing Length:**

Between 0.454 inches and 0.484 inches

**Body Width:**

Between 0.673 inches and 0.703 inches

**Body Height:**

Between 0.672 inches and 0.702 inches

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.237 inches and 0.243 inches

**Actuator Height:**

Between 0.673 inches and 0.703 inches

**Actuator Position-action Relationship:**

Up position momentary and down position maintained

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

3.000 amperes resistive dc and 1.500 amperes inductive dc and 3.000 amperes resistive ac and 1.500 amperes inductive ac

**Precious Material And Location:**

Terminal surfaces silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Specification Data:**

27914-2088678 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0