

View Online at <https://aerobasegroup.com/nsn/5930-01-279-4428>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.880 inches

**Body Length:**

1.090 inches

**Body Width:**

0.400 inches

**Body Height:**

0.630 inches

**Unthreaded Mounting Hole Diameter:**

0.130 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.410 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.110 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 6.0 ounces and 14.0 ounces

**Actuator Movement:**

Between 0.047 pretravel inches and 0.040 overtravel inches and 0.006 differential inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

0.250 amperes resistive dc and 15.100 amperes resistive ac and 5.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

3 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0