NSN 5930-01-279-7957

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-279-7957

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock resistant and driptight
Body Length:
0.975 inches
Body Width:
0.975 inches
Body Height:
3.150 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Armed/not; armed single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac
Special Features:

Horizontal split display

Precious Material And Location:

Terminal surfaces and housing finish gold

NSN 5930-01-279-7957

Push Switch - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity
----------------------------	----------	------	-----	----------

5 tab, solder lug and 12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0