

View Online at <https://aerobasegroup.com/nsn/5930-01-279-7957>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Shock resistant and driptight

**Body Length:**

0.975 inches

**Body Width:**

0.975 inches

**Body Height:**

3.150 inches

**Case Material:**

Metal

**Actuator Length:**

0.740 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.300 inches

**Actuator Width:**

0.740 inches

**Actuator Color:**

White single actuator and white single actuator

**Illuminated Actuator Color:**

Red single actuator and red single actuator

**Actuator Inscription:**

Armed/not; armed single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Features Provided:**

Rfi shielding

**Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

**Special Features:**

Horizontal split display

**Precious Material And Location:**

Terminal surfaces and housing finish gold

**Terminal Type And Quantity:**

5 tab, solder lug and 12 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0