NSN 5930-01-279-7958

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-279-7958

view Offilite at https://defobasegroup.com/hsh/0550-01-275-7550
Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and moisture resistant and salt spray resistant
Overall Length:
0.750 inches
Overall Height:
2.650 inches
Overall Width:
0.750 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Case Material:
Metal
Actuator Length:
0.750 inches
Actuator Style:
Rectangular
Actuator Width:
0.750 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and white single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 ampere
inductive ac and 1.500 amperes lamp ac
Special Features:

Contact surfaces gold and contacts silver

Precious Material And Location:

Horizontal split lens

NSN 5930-01-279-7958

Push Switch - Page 2 of 2



	U	Ina	ıble	То	De	cod	le:
--	---	-----	------	----	----	-----	-----

Unable to decode and unable to decode

Terminal Type And Quantity:

11 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0