NSN 5930-01-279-7958

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-279-7958

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Explosion proof and moisture resistant and salt spray resistant

Overall Length:

0.750 inches

Overall Height:

2.650 inches

Overall Width:

0.750 inches

Body Length:

0.740 inches

Body Width:

0.740 inches

Case Material:

Metal

Actuator Length:

0.750 inches

Actuator Style:

Rectangular

Actuator Width:

0.750 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

White single actuator and white single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes

inductive ac and 1.500 amperes lamp ac

Special Features:

Horizontal split lens

Precious Material And Location:

Contact surfaces gold and contacts silver

NSN 5930-01-279-7958

Push Switch - Page 2 of 2

Unable To Decode:

Unable to decode and unable to decode

Terminal Type And Quantity:

11 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

