

View Online at <https://aerobasegroup.com/nsn/5930-01-279-8032>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof and humidity resistant and salt spray resistant

**Overall Length:**

0.750 inches

**Overall Height:**

2.320 inches

**Overall Width:**

0.750 inches

**Body Length:**

0.688 inches

**Body Width:**

0.750 inches

**Body Height:**

2.120 inches

**Actuator Length:**

Between 0.510 inches and 0.650 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.150 inches

**Actuator Width:**

Between 0.510 inches and 0.650 inches

**Actuator Color:**

Black single actuator and black single actuator

**Illuminated Actuator Color:**

Green single actuator and green single actuator

**Actuator Inscription:**

Dg iins single actuator

**Maximum Voltage Rating In Volts:**

28.0 dc

**End Application:**

1520-01-082-0686 helicopter, electrical

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc

**Special Features:**

Horizontal split lens

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

**Specification Data:**

78286-65912-01820 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0