NSN 5930-01-279-8033

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-279-8033

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Dustproof and humidity resistant and salt spray resistant

Overall Length:

0.750 inches

Overall Height:

2.320 inches

Overall Width:

0.750 inches

Body Length:

0.688 inches

Body Width:

0.750 inches

Body Height:

2.120 inches

Actuator Length:

Between 0.510 inches and 0.650 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Width:

Between 0.510 inches and 0.650 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Green single actuator and green single actuator

Actuator Inscription:

Vg iins single actuator

Maximum Voltage Rating In Volts:

28.0 dc

End Application:

1520-01-082-0686 helicopter, electrical

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

 $2 \ \text{pole}, \ \text{double throw, both positions maintained single switch unit}$

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

NSN 5930-01-279-8033

Push Switch - Page 2 of 2



Special Features: Horizontal split lens **Precious Material And Location:** Contacts silver Terminal Type And Quantity: 6 turret and 5 tab, solder lug **Specification Data:** 78286-65912-01820 manufacturers source control Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A053a0