

View Online at <https://aerobasegroup.com/nsn/5930-01-280-2194>

Thread Class:

2b 1st mounting facility

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

10.183 inches

Overall Height:

Between 3.657 inches and 3.719 inches

Overall Width:

4.375 inches

Unthreaded Mounting Hole Diameter:

0.312 inches 2nd mounting facility

Distance Between Mounting Facility Centers:

3.812 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.609 inches 1st mounting facility

Mounting Method:

Bracket 2nd mounting facility and unthreaded hole 2nd mounting facility

Features Provided:

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

20 1st mounting facility

Thread Size:

0.250 inches 1st mounting facility

Contact Voltage Rating In Volts:

500.0 ac at sea level

Mounting Facility Pattern:

Two position in-line 2nd mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Criticality Code Justification:

Feat

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

30.0 amperes resistive load lowest dc voltage rating at sea level and 25.0 amperes inductive load lowest dc voltage rating at sea level

Special Features:

Item must comply with requirements of desc production standard no. L03998; for navy nuclear propulsion plant products only

Style Designator:

Tap, circuit selector

Thread Series Designator:

Unc 1st mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0