# NSN 5930-01-281-2277

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-2277

## **Body Style:**

Hole mounted

#### **Overall Length:**

0.626 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

0.208 inches

#### **Overall Height:**

0.780 inches

**Overall Width:** 

0.326 inches

**Body Length:** 

0.626 inches

### Body Width:

0.316 inches

### **Body Height:**

0.730 inches

# **Unthreaded Mounting Hole Diameter:**

0.091 inches

### Actuator Style:

Round

### Actuator Height:

0.445 inches

## **Actuator Free Position Height:**

0.445 inches

### Maximum Voltage Rating In Volts:

28.0 dc

### **End Application:**

Command assult amphibious vehicle (aavc-7a1).; assault amphibious vehicle, command (aavc-7a1)

### Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Unthreaded hole

### Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action single switch unit

#### Switch Release Force:

4.0 ounces

## Criticality Code Justification:

Feat

#### Switch Actuating Force:

Between 5.0 ounces and 17.0 ounces

#### **Actuator Movement:**

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

# NSN 5930-01-281-2277

Sensitive Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

## **Special Features:**

Weapon system essential

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0