NSN 5930-01-281-2277

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-2277

Body Style:
Hole mounted
Overall Length:
0.626 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.208 inches
Overall Height:
0.780 inches
Overall Width:
0.326 inches
Body Length:
0.626 inches
Body Width:
0.316 inches
Body Height:
0.730 inches
Unthreaded Mounting Hole Diameter:
0.091 inches
Actuator Style:
Round
Actuator Height:
0.445 inches
Actuator Free Position Height:
0.445 inches
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
Command assult amphibious vehicle (aavc-7a1).; assault amphibious vehicle, command (aavc-7a1)
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action single switch unit
Switch Release Force:
4.0 ounces
Criticality Code Justification:
Feat
Switch Actuating Force:
Between 5.0 ounces and 17.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

NSN 5930-01-281-2277

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0