

View Online at <https://aerobasegroup.com/nsn/5930-01-281-2292>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Dustproof and driptight

Overall Length:

0.960 inches

Overall Height:

2.360 inches

Overall Width:

0.960 inches

Body Length:

0.750 inches

Body Width:

0.680 inches

Body Height:

1.990 inches

Case Material:

Metal

Actuator Length:

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.150 inches

Actuator Width:

0.620 inches

Actuator Color:

Black single actuator and black single actuator

Illuminated Actuator Color:

Black single actuator and black single actuator

Actuator Inscription:

Hcff-12, avail/afff, start single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Horizontal split lens; actuator inscription in any acceptable color

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0