# NSN 5930-01-281-2297

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-2297

#### **Body Style:**

Panel mount

#### Hazardous Locations/environmental Protection:

Dustproof and driptight

#### **Overall Length:**

0.960 inches

#### **Overall Height:**

2.360 inches

#### **Overall Width:**

0.960 inches

#### **Body Length:**

0.750 inches

#### **Body Width:**

0.680 inches

#### **Body Height:**

1.990 inches

## Case Material:

Metal

## Actuator Length:

0.620 inches

#### Actuator Style:

Rectangular

#### Actuator Height:

0.150 inches

## Actuator Width:

0.620 inches

#### Actuator Color:

Black single actuator and black single actuator

#### Illuminated Actuator Color:

Black single actuator and black single actuator

#### **Actuator Inscription:**

Hcff-18, avail/afff, start single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### **Features Provided:**

Actuator seal

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-281-2297

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

## **Special Features:**

Horizontal split lens; actuator inscription in any acceptable color

**Precious Material And Location:** 

Contacts silver

#### **Terminal Type And Quantity:**

6 turret and 6 tab, solder lug

### Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A053a0