## NSN 5930-01-281-2299

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-2299

| ·   |
|---|
| Body Style:                                     |
| Panel mount                                     |
| Hazardous Locations/environmental Protection:   |
| Dustproof and driptight                         |
| Overall Length:                                 |
| 0.960 inches                                    |
| Overall Height:                                 |
| 2.360 inches                                    |
| Overall Width:                                  |
| 0.960 inches                                    |
| Body Length:                                    |
| 0.750 inches                                    |
| Body Width:                                     |
| 0.680 inches                                    |
| Body Height:                                    |
| 1.990 inches                                    |
| Case Material:                                  |
| Metal   |
| Actuator Length:                                |
| 0.620 inches                                    |
| Actuator Style:                                 |
| Rectangular                                     |
| Actuator Height:                                |
| 0.150 inches                                    |
| Actuator Width:                                 |
| 0.620 inches                                    |
| Actuator Color:                                 |
| Black single actuator and black single actuator |
| Illuminated Actuator Color:                     |
| Black single actuator and black single actuator |
| Actuator Inscription:                           |
| Hcff-20, avail/afff, start single actuator      |
| Maximum Voltage Rating In Volts:                |
| 115.0 ac and 28.0 dc                            |
| Inclosure Type:                                 |
| Fully enclosed                                  |
| Mounting Method:                                |
| Panel   |
| Features Provided:                              |
| Actuator seal                                   |
| Nonpile-up Contact Arrangement:                 |
|   |

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-281-2299

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

## **Special Features:**

Horizontal split lens; actuator inscription in any acceptable color

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

6 turret and 6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0