NSN 5930-01-281-2963

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-2963

3· · · · · · · · · · · · · · · · · · ·	
Body Style:	
Panel mount	
Hazardous Locations/environmental Protection:	
Dustproof and driptight	
Overall Length:	
0.960 inches	
Overall Height:	
2.360 inches	
Overall Width:	
0.960 inches	
Body Length:	
0.750 inches	
Body Width:	
0.680 inches	
Body Height:	
1.990 inches	
Case Material:	
Metal	
Actuator Length:	
0.620 inches	
Actuator Style:	
Rectangular	
Actuator Height:	
0.150 inches	
Actuator Width:	
0.620 inches	
Actuator Color:	
Black single actuator and black single actuator	
Illuminated Actuator Color:	
Black single actuator and black single actuator	
Actuator Inscription:	
Hcff-6, avail/afff, start single actuator	
Maximum Voltage Rating In Volts:	
115.0 ac and 28.0 dc	
Inclosure Type:	
Fully enclosed	
Mounting Method:	
Panel	
Features Provided:	
Actuator seal	
Nonpile-up Contact Arrangement:	

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-281-2963

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Horizontal split lens; actuator inscription in any acceptable color

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

6 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0