

View Online at <https://aerobasegroup.com/nsn/5930-01-281-3982>

Thread Class:

2b single mounting facility

Thread Length:

0.195 inches single mounting facility

Hazardous Locations/environmental Protection:

Dust resistant and explosion resistant and shock resistant and vibration resistant

Overall Length:

0.410 inches

Overall Height:

1.645 inches

Overall Width:

1.720 inches

Distance Between Mounting Facility Centers:

1.443 inches single mounting facility

Individual Section Quantity:

1

Mounting Method:

Base single mounting facility and threaded hole single mounting facility

Actuator Type:

Double push button all actuators

Thready Qty Per Inch (tpi):

56 single mounting facility

Thread Size:

0.086 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd with complement, 1 pole - 10 positions single section

Color:

White 2nd indicator marking

Style Designator:

Rectangular indicating

Test Data Document:

81349-mil-s-22710 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-s-22710/18 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0