

View Online at <https://aerobasegroup.com/nsn/5930-01-281-5017>

**Thread Class:**

2b single mounting facility

**Individual Section Quantity:**

8

**Longest Horizontal Distance Between Mounting Centers:**

2.297 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.297 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:**

Actuator knob

**Thready Qty Per Inch (tpi):**

24 single mounting facility

**Thread Size:**

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

8 single actuator

**Terminal Type:**

Screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

5.0 amperes resistive load highest ac voltage rating at sea level and 5.0 amperes inductive load highest ac voltage rating at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0