

View Online at <https://aerobasegroup.com/nsn/5930-01-281-5020>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

Between 0.340 inches and 0.380 inches

Overall Height:

Between 0.940 inches and 0.980 inches

Overall Width:

Between 0.300 inches and 0.340 inches

Bushing Length:

Between 0.200 inches and 0.240 inches

Body Length:

Between 0.340 inches and 0.380 inches

Body Width:

Between 0.300 inches and 0.340 inches

Body Height:

Between 0.320 inches and 0.360 inches

Case Material:

Plastic

Actuator Style:

Round

Actuator Diameter:

Between 0.080 inches and 0.120 inches

Actuator Height:

Between 0.270 inches and 0.310 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

48

Thread Size:

0.190 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0