## NSN 5930-01-281-5549

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-5549
Thread Class:
2b single mounting facility
Hazardous Locations/environmental Protection:
Humidity resistant
Overall Length:
6.282 inches
Overall Height:
3.750 inches
Overall Width:
3.750 inches
Individual Section Quantity:
6
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
7 each section periphery
Mounting Facility Circle Radius:
1.625 inches single mounting facility
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Thready Qty Per Inch (tpi):
24 single mounting facility
Thread Size:
0.190 inches single mounting facility
Contact Voltage Rating In Volts:
30.0 dc at sea level
Mounting Facility Pattern:
Four position circular single mounting facility
Switch Actuator Indexing Position Quantity:
7 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed-adjustable stops single actuator

## NSN 5930-01-281-5549

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

10.0 amperes resistive load dc at sea level

**Precious Material And Location:** 

Contact surfaces silver

**Precious Material:** 

Silver

Style Designator:

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0