NSN 5930-01-281-6887

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-281-6887

| Body Style: | | | | | | |
|--|--|--|--|--|--|--|
| Bushing mounted | | | | | | |
| Overall Length: | | | | | | |
| 2.250 inches | | | | | | |
| Overall Height: | | | | | | |
| 0.562 inches | | | | | | |
| Overall Width: | | | | | | |
| 0.562 inches | | | | | | |
| Body Diameter: | | | | | | |
| 0.562 inches | | | | | | |
| Actuator Diameter: | | | | | | |
| 0.344 inches | | | | | | |
| Actuator Height: | | | | | | |
| 0.281 inches | | | | | | |
| Actuator Color: | | | | | | |
| Orange single actuator | | | | | | |
| Illuminated Actuator Color: | | | | | | |
| Orange single actuator | | | | | | |
| Maximum Voltage Rating In Volts: | | | | | | |
| 115.0 ac and 28.0 dc | | | | | | |
| Inclosure Type: | | | | | | |
| Fully enclosed | | | | | | |
| Mounting Method: | | | | | | |
| Threaded bushing | | | | | | |
| Thready Qty Per Inch (tpi): | | | | | | |
| 32 | | | | | | |
| Thread Size: | | | | | | |
| 0.500 inches | | | | | | |
| Nonpile-up Contact Arrangement: | | | | | | |
| 1 pole, double throw, both positions maintained single switch unit | | | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | | | |
| 5.000 amperes resistive dc and 5.000 amperes resistive ac | | | | | | |
| Special Features: | | | | | | |
| 300 ohm resistor wired across terminal 2 and 4 | | | | | | |
| Precious Material And Location: | | | | | | |
| Contacts and terminals silver | | | | | | |
| Thread Series Designator: | | | | | | |
| Un | | | | | | |
| Terminal Type And Quantity: | | | | | | |
| 5 tab, solder lug | | | | | | |
| Shelf Life: | | | | | | |
| N/a | | | | | | |

NSN 5930-01-281-6887

Push Switch - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A053a0