

View Online at <https://aerobasegroup.com/nsn/5930-01-281-8160>

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 2.220 inches and 2.280 inches

Overall Height:

1.240 inches

Body Diameter:

0.640 inches

Body Height:

0.521 inches

Unthreaded Mounting Hole Diameter:

Between 0.212 inches and 0.218 inches

Distance Between Mounting Facility Centers:

Between 1.730 inches and 1.790 inches

Temperature Sensing Element Type:

Internal sensor

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Four position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

140.00 actuation point degrees fahrenheit and 120.00 deactuation point degrees fahrenheit

Contact Voltage Rating In Volts:

28.0 dc at sea level second voltage

Special Features:

Terminal board provided

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas

Style Designator:

Disc w/flange

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0