

View Online at <https://aerobasegroup.com/nsn/5930-01-281-8160>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Overall Length:**

Between 2.220 inches and 2.280 inches

**Overall Height:**

1.240 inches

**Body Diameter:**

0.640 inches

**Body Height:**

0.521 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.212 inches and 0.218 inches

**Distance Between Mounting Facility Centers:**

Between 1.730 inches and 1.790 inches

**Temperature Sensing Element Type:**

Internal sensor

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 500.0 degrees fahrenheit

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Hermetically sealed case

**Contact Action Stimulus:**

Increase

**Mounting Facility Pattern:**

Four position in-line

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

5.0 amperes resistive load second voltage and 2.5 amperes inductive load second voltage and 1.0 amperes lamp load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

140.00 actuation point degrees fahrenheit and 120.00 deactuation point degrees fahrenheit

**Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

**Special Features:**

Terminal board provided

**Frequency In Hertz:**

60.0 first voltage

**Media For Which Designed:**

Gas

**Style Designator:**

Disc w/flange

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0