

View Online at <https://aerobasegroup.com/nsn/5930-01-282-0032>

Hazardous Locations/environmental Protection:

Salt spray resistant

Overall Length:

0.625 inches

Overall Height:

8.875 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

8.250 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between 40.0 degrees fahrenheit and 125.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+0.15/+1.90 actuation point inches of water

Contact Voltage Rating In Volts:

480.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0