

View Online at <https://aerobasegroup.com/nsn/5930-01-282-0033>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.343 inches

Overall Height:

3.500 inches

Overall Width:

4.562 inches

Body Length:

2.187 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Distance Between Mounting Facility Centers:

2.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port and tamper proof cap

Contact Action Stimulus:

Increase

Proof Pressure:

3.00 pounds per square inch gage

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load first voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+0.07/+1.70 actuation point pounds per square inch gage and +0.02/+1.65 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point screw and internal deactuation point screw

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Special Features:

Stainless steel housing; individual adjustment screw for each circuit

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0