

View Online at <https://aerobasegroup.com/nsn/5930-01-282-0521>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

Between 3.147 inches and 3.239 inches

First Flat Length:

0.250 inches 2nd actuator

Shaft Diameter:

0.248 inches 1st actuator and 0.251 inches 1st actuator

Shaft Length:

0.750 inches 2nd actuator

Overall Diameter:

0.687 inches

Individual Section Quantity:

3

Switch Contact Basic Design:

Coded

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

30.0 dc at sea level

Shaft Flat/slot Angular Location:

72.0 degrees from contact position 1 1st actuator

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round, hollowed 1st actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

36.0 degrees single actuator

Detent Rotational Torque Range:

+4.000/+32.000 inch-ounces all actuators

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact silver and contact and terminal surface gold

Precious Material:

Silver and gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0