NSN 5930-01-282-1967

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-282-1967

Overall Length:
6.040 inches
Overall Height:
3.250 inches
Overall Width:
3.250 inches
Unthreaded Mounting Hole Diameter:
0.201 inches single mounting facility and 0.221 inches single mounting facility
Individual Section Quantity:
3
Knob Manufacturer Code:
82121
Knob Manufacturer Part Number:
02000-12
Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact surfaces silver

NSN 5930-01-282-1967

Rotary Switch - Page 2 of 2



P	reci	nus	Materia	ŀ

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0