

View Online at <https://aerobasegroup.com/nsn/5930-01-282-2388>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.375 inches single mounting facility

**Overall Length:**

4.189 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

1.025 inches single actuator

**Overall Diameter:**

1.625 inches

**Nonturn Device Radius:**

0.531 inches at 5:00 o'clock

**Individual Section Quantity:**

4

**Nonturn Device Type:**

Pin at 5:00 o'clock

**Operating Temperature Range:**

-25.0/+85.0 degrees celsius

**Switch Contact Basic Design:**

Nonpile-up symmetrical and nonpile-up nonsymmetrical

**Pole Quantity:**

2 3rd section front

**Throw Quantity:**

4 1st section front

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

4 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0