NSN 5930-01-282-2405

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-282-2405

· · · · · · · · · · · · · · · · · · ·			
Hazardous Locations/environmental Protection:			
Waterproof			
Overall Length:			
5.220 inches			
Overall Height:			
2.910 inches			
Overall Width:			
2.810 inches			
Unthreaded Mounting Hole Diameter:			
0.201 inches single mounting facility			
Individual Section Quantity:			
2			
Knob Manufacturer Code:			
82121			
Knob Manufacturer Part Number:			
02000-12			
Longest Horizontal Distance Between Mounting Centers:			
2.000 inches single mounting facility			
Shortest Horizontal Distance Between Mounting Centers:			
1.000 inches single mounting facility			
Longest Vertical Distance Between Mounting Centers:			
2.188 inches single mounting facility			
Switch Contact Basic Design:			
Nonpile-up nonsymmetrical			
Mounting Method:			
Bracket single mounting facility and unthreaded hole single mounting facility			
Features Provided:			
Actuator knob and legend plate			
Contact Voltage Rating In Volts:			
600.0 highest ac voltage rating at sea level			
Switch Actuator Momentary Position:			
Clockwise single actuator and counterclockwise single actuator			
Mounting Facility Pattern:			
Isosceles triangle single mounting facility			
Switch Actuator Indexing Position Quantity:			
3 single actuator			
Terminal Type:			
Tab w/screw			
Contact Switching Action:			
Breaks before makes each section periphery			
Switch Actuator Positioning Increment:			

45.0 degrees single actuator

NSN 5930-01-282-2405

Rotary Switch - Page 2 of 2



Contact	Load	Current	Rating:
---------	------	---------	---------

6.0 amperes resistive load highest ac voltage rating at sea level

Special Features:

Legend plate reads lower, hold, raise

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0