

View Online at <https://aerobasegroup.com/nsn/5930-01-282-3130>

Body Style:

Panel mount

Body Length:

1.030 inches

Body Width:

0.840 inches

Body Height:

2.080 inches

Actuator Length:

0.770 inches

Actuator Style:

Rectangular

Actuator Height:

0.370 inches

Actuator Width:

0.600 inches

Actuator Color:

Red single actuator

Illuminated Actuator Color:

Red single actuator

Actuator Inscription:

Power single actuator

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Dwicheita class aor, spruance class d (963) , oliver perry class ffg, forrestal class cv, emoru s.Land class as, whidbey island class lsd, nimitz class cvn, cimmaron class ao, wasp class lhd, tarawa class, lha

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Special Features:

Weapon system essential

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

5 quick disconnect, male or 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0