

View Online at <https://aerobasegroup.com/nsn/5930-01-282-3130>

**Body Style:**

Panel mount

**Body Length:**

1.030 inches

**Body Width:**

0.840 inches

**Body Height:**

2.080 inches

**Actuator Length:**

0.770 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.370 inches

**Actuator Width:**

0.600 inches

**Actuator Color:**

Red single actuator

**Illuminated Actuator Color:**

Red single actuator

**Actuator Inscription:**

Power single actuator

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Dwicheita class aor, spruance class d (963) , oliver perry class ffg, forrestal class cv, emoru s.Land class as, whidbey island class lsd, nimitz class cvn, cimmaron class ao, wasp class lhd, tarawa class, lha

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Criticality Code Justification:**

Feat

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Special Features:**

Weapon system essential

**Precious Material And Location:**

Contacts silver

**Terminal Type And Quantity:**

5 quick disconnect, male or 5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0