

View Online at <https://aerobasegroup.com/nsn/5930-01-282-3922>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

6.250 inches

Overall Height:

3.680 inches

Overall Width:

3.750 inches

Unthreaded Mounting Hole Diameter:

0.280 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

5.500 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

3.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Pole Quantity:

1 single section front

Throw Quantity:

1 single section front

Mounting Method:

Flange single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob and legend plate

Contact Voltage Rating In Volts:

440.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

2 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

1.1 amperes inductive load lowest dc voltage rating at sea level

Special Features:

Legend plate reads: stop, run

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0