

View Online at <https://aerobasegroup.com/nsn/5930-01-282-3922>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

6.250 inches

**Overall Height:**

3.680 inches

**Overall Width:**

3.750 inches

**Unthreaded Mounting Hole Diameter:**

0.280 inches single mounting facility

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

5.500 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Pole Quantity:**

1 single section front

**Throw Quantity:**

1 single section front

**Mounting Method:**

Flange single mounting facility and unthreaded hole single mounting facility

**Features Provided:**

Actuator knob and legend plate

**Contact Voltage Rating In Volts:**

440.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Terminal Type:**

Tab w/screw

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Contact Load Current Rating:**

1.1 amperes inductive load lowest dc voltage rating at sea level

**Special Features:**

Legend plate reads: stop, run

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0