## NSN 5930-01-282-4643

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-282-4643

**Thread Class:** 

2a single mounting facility

**Overall Length:** 

4.840 inches

**Overall Height:** 

2.910 inches

**Overall Width:** 

2.810 inches

**Individual Section Quantity:** 

1

**Longest Horizontal Distance Between Mounting Centers:** 

2.000 inches single mounting facility

**Shortest Horizontal Distance Between Mounting Centers:** 

1.000 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:** 

2.180 inches single mounting facility

**Switch Contact Basic Design:** 

Nonpile-up nonsymmetrical

**Mounting Method:** 

Bracket single mounting facility and threaded hole single mounting facility

**Features Provided:** 

Legend plate and actuator knob

**Thread Size:** 

0.190 inches single mounting facility

**Contact Voltage Rating In Volts:** 

500.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:** 

Isosceles triangle single mounting facility

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Terminal Type:** 

Screw

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

**Contact Load Current Rating:** 

5.0 amperes resistive load highest ac voltage rating at sea level

**Special Features:** 

Legend plate reads: gen heater, off, on

**Precious Material And Location:** 

Rotor and stator surfaces silver

**Precious Material:** 

Silver

## NSN 5930-01-282-4643

Rotary Switch - Page 2 of 2



Sty	le [	)es	ign	ato	r:

Tap, square frame

**Thread Series Designator:** 

Unf single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0