NSN 5930-01-282-6925

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-282-6925

View Online at https://aerobasegroup.com/nsn/5930-01-282-6925
Overall Length:
5.220 inches
Overall Height:
2.910 inches
Overall Width:
2.810 inches
Individual Section Quantity:
2
Longest Horizontal Distance Between Mounting Centers:
2.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
2.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 each section periphery
Throw Quantity:
7 each section periphery
Mounting Method:
Bracket single mounting facility
Features Provided:
Actuator knob and legend plate
Contact Voltage Rating In Volts:
600.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Screw
Contact Switching Action:
Breaks before makes each section periphery
Switch Actuator Positioning Increment:
45.0 degrees single actuator
Switch Actuator Stop Device Type:
Adjustable stop single actuator
Contact Load Current Rating:
6.0 amperes resistive load highest ac voltage rating at sea level
Precious Material And Location:

Contact surfaces silver

NSN 5930-01-282-6925

Rotary Switch - Page 2 of 2



Praci	ious	IVI 2†6	riai.
	lous	ıvıaıc	ııaı.

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0