NSN 5930-01-282-7850

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-282-7850

Hannadava I andianalawinawantal Partestiana
Hazardous Locations/environmental Protection: Vibration resistant
Overall Length:
3.240 inches
Body Diameter:
Between 0.525 inches and 0.565 inches
Body Length:
2.140 inches
Tempurature Sensing Element Type:
Immersion well
Width Across Flats:
0.688 inches
Operating Tempurature Rating:
Between 15.0 degrees fahrenheit and 550.0 degrees fahrenheit
Mounting Method:
Threaded bushing
Features Provided:
Hermetically sealed case
Contact Action Stimulus:
Increase
Thread Size:
0.375 inches single threaded bushing
Nonpile-up Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
5.0 amperes resistive load first voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
120.00 actuation point degrees fahrenheit and 100.00 deactuation point degrees fahrenheit
Contact Voltage Rating In Volts:
240.0 ac at sea level second voltage
-
Frequency In Hertz:
60.0 second voltage
Media For Which Designed:
Gas or liquid
Precious Material And Location:
Contacts silver
Precious Material:
Silver

NSN 5930-01-282-7850

Thermostatic Switch - Page 2 of 2



Style	Design	nator:

Cylindrical w/flange

Thread Series Designator:

Nptf single threaded bushing

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A048b0