## NSN 5930-01-283-0222

Push Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-283-0222 **Body Style:** Panel mount **Overall Length:** 1.200 inches **Overall Height:** 2.962 inches **Overall Width:** 0.960 inches **Body Length:** 0.844 inches **Body Width:** Between 0.835 inches and 0.865 inches **Body Height:** 2.762 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Panel **Features Provided:** Rfi shielding **Nonpile-up Contact Arrangement:** 2 pole, double throw, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac **Test Data Document:** 81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 5 turret and 5 tab, solder lug **Specification Data:** 81349-mil-s-22885/87 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

Fiig: A053a0

No