

View Online at <https://aerobasegroup.com/nsn/5930-01-283-4370>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Hazardous Locations/environmental Protection:**

Splashproof

**Overall Length:**

0.890 inches

**Overall Height:**

1.700 inches

**Overall Width:**

0.510 inches

**Bushing Length:**

0.280 inches

**Body Length:**

0.890 inches

**Body Width:**

0.510 inches

**Body Height:**

0.780 inches

**Case Material:**

Plastic

**Actuator Style:**

Round

**Actuator Diameter:**

0.250 inches

**Actuator Height:**

0.480 inches

**Maximum Voltage Rating In Volts:**

28.0 dc and 250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing w/panel seal

**Features Provided:**

Actuator seal and o ring

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.250 inches

**Nonpile-up Contact Arrangement:**

4 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

4.000 amperes resistive dc and 3.000 amperes resistive ac

**Precious Material And Location:**

Contacts and terminals silver and contacts and terminal surfaces gold

**Unable To Decode:**

Unable to decode and unable to decode

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0