

View Online at <https://aerobasegroup.com/nsn/5930-01-283-4431>

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Longest Horizontal Distance Between Mounting Centers:**

3.000 inches

**Longest Vertical Distance Between Mounting Centers:**

3.625 inches

**Pressure Switch Type:**

Differential

**Mounting Method:**

Flange and unthreaded hole

**Features Provided:**

Electrical access port

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

1000.00 pounds per square inch

**Mounting Facility Pattern:**

Four position rectangular

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

15.0 amperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+3.00/+30.00 actuation point pounds per square inch

**Contact Voltage Rating In Volts:**

480.0 ac at sea level second voltage

**Frequency In Hertz:**

60.0 second voltage

**Media For Which Designed:**

Gas or liquid

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0