

View Online at <https://aerobasegroup.com/nsn/5930-01-283-5286>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Body Diameter:**

0.562 inches

**Bushing Length:**

0.425 inches

**Body Length:**

1.130 inches

**Case Material:**

Metal

**Actuator Length:**

0.500 inches

**Actuator Style:**

Rectangular

**Actuator Height:**

0.440 inches

**Actuator Width:**

0.500 inches

**Illuminated Actuator Color:**

Red single actuator

**Actuator Inscription:**

2 single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

**Precious Material And Location:**

Contacts silver

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0