

View Online at <https://aerobasegroup.com/nsn/5930-01-283-5290>

Thread Class:

2a

Body Style:

Bushing mounted

Body Diameter:

0.562 inches

Bushing Length:

0.425 inches

Body Length:

1.130 inches

Case Material:

Metal

Actuator Length:

0.500 inches

Actuator Style:

Rectangular

Actuator Height:

0.440 inches

Actuator Width:

0.500 inches

Illuminated Actuator Color:

Red single actuator

Actuator Inscription:

0 single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0