NSN 5930-01-283-6909

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-283-6909

| Body Style: |
|---|
| Hole mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 1.156 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.937 inches |
| Overall Height: |
| 0.997 inches |
| Overall Width: |
| 0.450 inches |
| Body Length: |
| 0.500 inches |
| Body Width: |
| 0.450 inches |
| Body Height: |
| 0.430 inches |
| Actuator Length: |
| 0.531 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.310 inches |
| Actuator Width: |
| 0.365 inches |
| Actuator Position-action Relationship: |
| Left position maintained and right position momentary |
| Actuator Color: |
| Black single actuator |
| Maximum Voltage Rating In Volts: |
| 20.0 ac and 20.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 20.000 milliamperes resistive dc and 20.000 milliamperes resistive ac |

Precious Material And Location:

Contact and terminal surfaces gold

NSN 5930-01-283-6909

Toggle Switch - Page 2 of 2



| Terminal Type Aı | nd Quantity: |
|------------------|--------------|
|------------------|--------------|

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0